


Rotating laser ECO/4

The robust horizontal laser
for the construction site

Delivered with receiver and
rod clamp as a standard



®

Precise surveying
and measuring

Rotating laser ECO/4



Ref.-No. 460 942-613

The self-levelling rotating laser ECO/4 sets new standards in its category. Its robust design makes the ECO/4 an ideal helper on every construction site. Thanks to its easy handling (just one button to operate), it is ready for use in no time. The ECO/4 levels itself reliably via pendulum.

- Robust horizontal laser
- Reliable self-levelling via pendulum
- One-button operation
- Automatic switch-off when self-levelling range is exceeded
- Can be used with rechargeable batteries

Delivery includes

- Rotating laser
- Laser receiver with rod clamp
- Batteries for laser and receiver
- User manual
- Transport case

Technical data laser

Self-levelling range:	± 10'
Accuracy:	±1 mm/10 m
Laser type:	< 1 mW, laser class 2, 635-670 nm
Rough adjustment with spirit level and tribrach:	8 1/2 mm
Power supply:	4 x 1.5 V batteries (C/LR14)
Operation duration:	approx. 30 h
Weight:	approx. 2.36 kg
Dimensions:	165 mm x 160 mm x 250 mm
Working temperature:	-10°C up to +50°C
Working range (with receiver):	approx. 150 m
Rotating speed:	approx. 360 rpm
Protection class:	IP 53
Ref.-No.	460 942-613



Laser receiver included in delivery



- Large, illuminable LCD display on front and back
- Display of remaining battery power
- Two accuracy modes
- Adjustable volume of audible signal
- Rod clamp for laser receiver

Technical data laser receiver

Accuracy:	± 1.0 mm / ± 2.5 mm
Power supply:	9 V battery
Operation duration:	approx. 30 h
Automatic switch-off:	after 30 min
Weight (incl. batteries):	210 g
Dimensions:	75 mm x 30 mm x 170 mm



Rotating laser set ECO/4 Ref.-No. 460 943

with aluminium tripod.....200 200-613
flexi rod.....360 811-622
and universal adapter.....360 515-613



**Precise surveying
and measuring**

Nedo GmbH & Co. KG
Hochgerichtstrasse 39-43 D-72280 Dornstetten
Germany
Phone: 07443 / 2401-0 Fax: 07443 / 2401-45

Your Nedo-Dealer